

# Wall-Mounted Housing WM



WM stainless steel Page 171 WM stainless steel, with roof slope Page 174

### Material:

- Housing: Stainless steel 1.4301 (AISI 304)
- Door: Stainless steel 1.4301 (AISI 304), all-round foamed-in PU seal
- Mounting plate: Carbon steel

### Surface finish:

- Housing and door: Brushed, grain 240
- Mounting plate: Zinc-plated

### Protection category IP to IEC 60 529:

- IP 55
- IP 66

### Protection category NEMA:

- NEMA 12, 3R, 4X

### Approvals:


- UL
- cUL

### Supply includes:

- Housing with hinged door(s), of all-round solid construction, door catch on the left on single-door housing
- Universal disconnect cutout
- Mounting plate
- Blind rivet nuts for wall mounting
- 2- or 3-point latching L-handle

### Technical details:

Available on the Internet



## Stainless Steel, for Isolator Lock

Height (H) inches (mm)	Packs of	24 (600)	35 (900)	41 (1050)	47 (1200)	Page
Width (B) inches (mm)		26 (650)	32 (825)	32 (825)	38 (975)	
Depth (T) inches (mm)		8 (210)	12 (300)	12 (300)	16 (400)	
Mounting plate height (G) inches (mm)		22 (570)	34 (870)	40 (1020)	45 (1155)	
Mounting plate width (F) inches (mm)		22 (549)	28 (704)	33 (840)	33 (840)	
Material thickness, housing ga (mm)		16 (1.5)	14 (2.0)	14 (2.0)	14 (2.0)	
Material thickness, door ga (mm)		14 (2.0)	14 (2.0)	14 (2.0)	14 (2.0)	
<b>Model No.</b>	1 pc(s).	<b>8018.627</b>	<b>8018.633</b>	<b>8018.629</b>	<b>8018.634</b>	
<b>Model No. US</b>	1 pc(s).	<b>WM242608X4</b>	<b>WM363212X4</b>	<b>WM423212X4</b>	<b>WM483816X4</b>	
Door(s)		1	1	1	1	
Locking points		2	2	3	3	
Weight lb (kg)		57 (26)	124 (56)	163 (74)	207 (94)	
<b>Accessories</b>						
Wall mounting bracket	4 pc(s).	2433.000	2433.000	2433.000	2433.000	504
L-handle	1 pc(s).	8018.691	8018.691	8018.691	8018.691	487