



## Class 52 Oiltight pilot devices

Siemens 30mm NEMA pilot devices are designed to provide long, trouble-free service in the most demanding applications. Durable plastic Metal Operators with plastic buttons resist oils while internally, contact blocks have double break bifurcated silver contacts which improve overall performance.

### COMMON 30mm SELECTOR SWITCH



> **52SA2AAB | US2:52SA2AAB**  
Selectorswitch, metal Maintained, short lever position, A Cam 2 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



> **52SA2ACB | US2:52SA2ACB**  
SWITCH\_COMMAND 52SA2ACB-ROT\_RET



> **52SA2CAB | US2:52SA2CAB**  
Metal, selector switch Maintained, short lever Position, C Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

> **52SA2BBB | US2:52SA2BBB**  
Selector switch, metal Spring return from left Short lever position, B Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



> **52SA2BDB | US2:52SA2BDB**  
Selector switch, metal Spring return left & right Short lever position, B Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



> **52SA2AAB | US2:52SA2AAB**  
Selectorswitch, metal Maintained, short lever position, A Cam 2 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



> **52SA2ACB | US2:52SA2ACB**  
SWITCH\_COMMAND 52SA2ACB-ROT\_RET



> **52SA2BAB | US2:52SA2BAB**  
Metal, selector switch Maintained, short lever position, B Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

> **52SA2BBB | US2:52SA2BBB**  
Selector switch, metal Spring return from left Short lever position, B Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



> **52SA2BDB | US2:52SA2BDB**  
Selector switch, metal Spring return left & right Short lever position, B Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Tel. 705-682-2828

Website: [www.chesscontrols.com](http://www.chesscontrols.com)